

800 Series Regulators

Variflow Regulators



Calgaz, the world's leading manufacturer of calibration gases and equipment is proud to offer the most comprehensive range of specialist regulators in the world for non-refillable and portable gas cylinders.

The 800 series regulators have 4 different models including low/high pressure applications and brass/stainless steel body.

These variflow regulators can have selectable flow rates including: 0.5 | 0.75 | 1.0 | 1.5 | 2.0 | 2.5 | 3.0 | 4.0 | 5.0LPM

All regulators carry a 24 month warranty and we recommend replacing them after 5 years of service and can often be shipped to you the next working day. Contact us to find out more information.

If you want to to find out more information or get a quote, please contact us at: info@calgaz.com



| PERFORMANCE | | | | | | | |
|-------------|-----------------|-----------------------|-----------------------------|--------|-----------------------|------------------------|--|
| | Inlet | Outlet | Variflow | Stages | Max Inlet Pressure | Max Outlet Pressure | |
| 801 | C 10 | 4.8mm (3/16") Barb | 0.5 Lit/Mn to 5.0 Lit/Mn | 2 | 70 Bar (1000 Psi) | 4.1 Bar (60 Psi) | |
| 802 | 1/4" NPT Female | 4.8mm (3/16") Barb | 0.5 Lit/Mn to 5.0 Lit/Mn | 2 | 275 Bar (4000 Psi) | 4.1 Bar (60 Psi) | |
| 803 | C 10 | 4.8mm (3/16") Barb | 0.5 Lit/Mn to 5.0 Lit/Mn | 2 | 70 Bar (1000 Psi) | 4.1 Bar (60 Psi) | |
| 804 | 1/4" NPT Female | 4.8mm (3/16") Barb | 0.5 Lit/Mn to 5.0 Lit/Mn | 2 | 275 Bar (4000 Psi) | 4.1 Bar (60 Psi) | |

| MATERIALS OF CONSTRUCTION | | | | | | |
|---------------------------|------------------|------------------|-------------|--------|-----------------|--|
| | Body | Piston | Piston Seal | Seat | Weight | |
| 801 | Brass Forged | Brass Forged | Viton | Teflon | 0.26kg (0.57lb) | |
| 802 | Brass Forged | Brass Forged | Viton | Teflon | 0.32kg (0.7lb) | |
| 803 | Brass Forged /SS | Brass Forged /SS | Viton | Teflon | 0.26kg (0.57lb) | |
| 804 | Brass Forged /SS | Brass Forged /SS | Viton | Teflon | 0.32kg (0.7lb) | |

| GAS SUITABILITY | | | | | | |
|-----------------|--------------|-----------|-----------------|-----------------------------------|--|--|
| | Non-Reactive | H2S & S02 | NO & NO2 | CI2 , HCL, NH3, PH3,SiH4 & HCN | | |
| 801 | Suitable | Suitable | Not recommended | Not recommended | | |
| 802 | Suitable | Suitable | Not recommended | Not recommended | | |
| 803 | Suitable | Suitable | Suitable | Suitable | | |
| 804 | Suitable | Suitable | Suitable | Suitable | | |

| CYLINDERS COMPATIBILITY | | | | | | | |
|-------------------------|-----|------|----|-----|-----|------|-------|
| | 2AL | 5ELR | 6D | 6DM | 8AL | 10AL | 65ALR |
| 801 | 1 | | 1 | 1 | 1 | 1 | |
| 802 | | 1 | | | | | 1 |
| 803 | 1 | | 1 | 1 | 1 | 1 | |
| 804 | | 1 | | | | | 1 |

For more information contact us at:

info@calgaz.com

or

Tel: +1 800 638 1197 (US)
Tel: +44 1782 566897 (UK)
Tel: +971 56 131 2346 (UAE)
Tel: +65 62653788 (SG)
Tel: +86 21 6090 3711 (CN)

